



Date: 11/01/97
Revision: B
Approved: BOD

AT-6/SNJ Specification Sheet

WING	MODEL MINIMUM
SPAN	100"
ROOT CHORD (@ C/L OF FUSELAGE)	18"
TIP CHORD	9 1/2"
ROOT THICKNESS	2 11/16"
TIP THICKNESS	1 3/16"
STAB	
SPAN	31 1/16"
ROOT CHORD (@ WIDEST POINT)	11"
TIP CHORD (@ ELEVATOR COUNTERBALANCE)	7 3/16"
ROOT THICKNESS	1 5/16"
TIP THICKNESS (1" FROM END)	1/2"
COWL	
DIAMETER	10 3/4"
CIRCUMFERENCE (= DIAM. x 3.14)	33 3/4"
LENGTH	5 1/2" MIN, 7 1/2" MAX
TRAILING EDGE GAP	1/4"
SPINNER	
DIAMETER	3 1/4"
FUSELAGE	
LENGTH (OVERALL - SPINNER TO END OF RUDDER)	70" MIN, 73 1/2" MAX
WIDTH AT FIREWALL	10"
WIDTH AT TRAILING EDGE OF WING	8 3/4"
HEIGHT FROM CANOPY TOP TO FUSELAGE BOTTOM	15 3/4"
HEIGHT OF RUDDER @ HINGE LINE	15 3/4"
WHEELS/TIRES	
MAINS (DIAMETER x WIDTH)	5" x 1 1/2"
TAILWHEEL (DIAMETER x WIDTH)	2 1/4" x 1/2"